



1685 CROSSTOWN BOULEVARD N.W. • ANDOVER, MINNESOTA 55304 • (763) 755-5100
FAX (763) 755-8923 • WWW.ANDOVERMN.GOV

Tree Fence Requirements Per Tree Preservation Policy

- Tree protection should be installed at drip line of tree(s).
- 4-foot tall orange poly fence is acceptable.
- 4-inch wide ribbon may be used for passive tree protection in some instances.
- All sub-contractors must respect tree protection.
- Tree protection is to be maintained throughout the whole construction process to ensure necessary protection of the valuable trees.
- A penalty will be assessed to the violator causing significant damage to trees originally under tree protection.

Tree Fence Recommendations

- It is encouraged that you contact Natural Resources Technician for consultation.
- Tree protection is needed if trees are within 50 ft. of the construction zone.
- Orange silt/tree fence with wood stakes is acceptable for tree protection of an entire development.
- Stakes used to hold up fence should be no more than 10 feet apart from one another.
- Stakes must be steel and at least 4 and ½ feet tall (if 4 foot tall poly fence is used).
- Fence must be adequately secured to the stakes.
- Fence should be sturdy and act as an effective barrier.

(Over)

- **AVOID WOUNDING OAKS FROM APRIL THRU SEPTEMBER; CONTACT NATURAL RESOURCES TECHNICIAN BEFORE CLEARING OAKS DURING THIS TIME PERIOD.**
- **LET'S WORK TOGETHER AND TRY AND SAVE SOME TREES.**
 - The benefits they provide are immeasurable.
 - Most trees are pretty sensitive to construction damage, so respect their space.
 - Make an extra effort to protect them.